

VIBEX-HP Specification

1. Vibex-HP Spec Details, Part N° PDG-006

Test Name	Method	Max	Typical	Min
Density, g/cm ³	ASTM D1298		0.874	
Brookfield Vis, 20 rpm @ 25°C, cP	ASTM D2983	570K	510K	450K
Brookfield Vis, 100 rpm @ 25°C, cP	ASTM D2983	180K	140K	100K
Cone Penetration	ASTM D217	225	200	175
Water Resistance, % spray	ASTM D4049		Pass	
Flash Point, °C	ASTM D92		280	260
Pour Point, °C	ASTM D97		-30	-25
Oil Bleed Out, % weight	IPI 121	0.15	<0.1	
Water resistance, 54.5°C, 22hrs	Internal		Pass	
Pounds/ gallon	Conversion		7.29	

Key characteristic are shown in red font

With proper venting, operating temp can be raised

2. Typical Temperature Range

-30°C to 60°C

3. Appearance

Colorless Translucent with dispersed red particle

4. Packaging

Pail.....Plastic with light blue lid

Net Weight.....16Kg

5. Label Information

Permawick Part Number

Customer Part Number

Lot Number / Individual Bag Number

Date of Manufacture

Quantity (Net Weight)

Color Coding